




COLOrAdo™ Zoom Tour

SPECIFICATIONS & FEATURES

CHAUVET®



AT A GLANCE:

RGBW Color Mixing



Key Features:

- 37, 2&3 W RGBW CREE LEDs deliver huge output with the ability to show the most subtle pastels.
- 8~27.5 degree zoom allows for programming versatility in keeping light where its needed.
- Silent, fan-free operation allows for use in noise sensitive environments
- Direct 3 & 5-pin DMX in/out and powerCON in/out make connections a breeze.
- Flicker free performance, makes the fixture safe for use on camera
- Built-in color temperature presets provide predictable color every time.

About this light:

COLOrAdo™ Zoom Tour is an LED-powered wash with a variable zoom and 37 2- and 3-watt RGBW CREE LEDs. The 8- to 27.5-degree zoom can highlight specific areas or flood the stage. This silent fixture boasts a rugged aluminum housing that cools the fixture without the aid of fans. Secure Neutrik® powerCON® in-and-out, as well as direct DMX connections make hanging and hook-up a breeze.

DETAILED SPECIFICATIONS:

Features

- DMX channels: 3, 4, 5, 6 or 12
- Operating modes:
 - 3-channel: Red, Green, Blue (ARC 1)
 - 3-channel: Hue, Saturation, Value (HSV)
 - 4-channel: Dimmer, Red, Green, Blue (ARC 1+D)
 - 4-channel: Red, Green, Blue, White (ARC 2)
 - 5-channel: Dimmer, Red, Green, Blue, White (ARC 2+D)
 - 6-channel: Dimmer, Red, Green, Blue, White, Strobe (ARC 2+S)
 - 12-channel: Dimmer, Red, Green, Blue, White, Color Macro, Strobe, Auto Programs, Auto Speed Adjust, Dimmer Speed, Zoom, Zoom Reset (TOUR)
- RGBW color mixing and zoom control with or without DMX control
- Color temperature presets (3,200 ~ 10,000 K)
- 8°- 27.5° zoom control with or without DMX control
- Built-in automated programs via master/slave or DMX
- Recall custom programs via master/slave or DMX
- Five distinct dimming curves
- RGBW LEDs
- Electronic dimmer
- Color macros with speed adjustment included
- Electronic power supply
- Neutrik powerCon connectors
- 3-pin and 5-pin DMX input and output connectors
- Additional power output: max 7 units @ 120 V / 12 units @ 208 V / 14 units @ 230 V
- LED display with password protection
- Gel frame holder (4 mm max thickness)
- Double-bracket yoke doubles as floor stand
- Color Calibration
- Flicker free operation for HD Video

Specifications

- DMX connectors: 3-pin & 5-pin
- Source: 37 LEDs: 37 (2 and 3 W) LEDs, 50,000 hours
- Configuration: 10 Red (.664 A x 2.294 VDC = 1.52 W)
10 Green (.952 A x 3.380 VDC = 3.21 W)
10 Blue (.944 A x 3.351 VDC = 3.16 W)
7 White (.964 A x 3.239 VDC = 3.12 W)
- Beam angle: 8°~ 27.5°
- Field angle: 15°~ 42°
- Lux: 3,171 (8°) - 310 (27.5°) @ 5 m
- Cable length: 5 ft (1.5 m)
- Power linking: 7 units @ 120 V / 12 units @ 208 V / 14 units @ 230 V
- AC Voltage Range: 100~240 V, 50/60 Hz (auto-ranging)
- Power Consumption 120 V, 60 Hz: 132 W, 1.026 A (operating)
- Power Consumption 208 V, 60 Hz: 124 W, 0.637 A (operating)
- Power Consumption 230 V, 50 Hz: 122 W, 0.566 A (operating)
- Dimensions: 7.9 x 9.8 x 13.1 in (203 x 250 x 334 mm)
- Weight: 15.1 lbs (6.84 kg)
- Certification: CE, MET
- Environment: IP20, dry location

www.chauvetlighting.com
www.chauvetlighting.co.uk

CHAUVET®